

Maximum Allowable Heights for Drywall Stud Sections

1 5/8" x 25ga x 33 KSI					1 5/8" x 22ga x 33 KSI					1 5/8" x 20ga x 33 KSI				
Spc (in.)	Wind Px psf	L120 ft.	L240 ft.	L360 ft.	Spc (in.)	Wind Px psf	L120 ft.	L240 ft.	L360 ft.	Spc (in.)	Wind Px psf	L120 ft.	L240 ft.	L360 ft.
12	5.00	10.1	8.0	7.0	12	5.00	11.6	9.2	8.1	12	5.00	12.4	9.8	8.6
12	6.70	9.1	7.3	6.3	12	6.70	10.6	8.4	7.3	12	6.70	11.3	8.9	7.8
12	7.50	8.8	7.0	6.1	12	7.50	10.2	8.1	7.1	12	7.50	1.8	8.6	7.5
12	10.00	8.0	6.3	5.5	12	10.00	9.2	7.3	6.4	12	10.00	9.8	7.8	6.8
12	12.50	7.4	5.9	5.1	12	12.50	8.6	6.8	6.0	12	12.50	9.1	7.2	6.3
12	15.00	7.0	5.5	4.8	12	15.00	8.1	6.4	5.6	12	15.00	8.6	6.8	6.0
12	20.00	6.0	5.0	4.4	12	20.00	7.3	5.8	5.1	12	20.00	7.8	6.2	5.4
16	5.00	9.1	7.3	6.3	16	5.00	10.6	8.4	7.3	16	5.00	11.3	8.9	7.8
16	6.70	8.3	6.6	5.8	16	6.70	9.6	7.6	6.7	16	6.70	10.2	8.1	7.1
16	7.50	8.0	6.3	5.5	16	7.50	9.2	7.3	6.4	16	7.50	9.8	7.8	6.8
16	10.00	7.3	5.8	5.0	16	10.00	8.4	6.7	5.8	16	10.00	8.9	7.1	6.2
16	12.50	6.6	5.3	4.7	16	12.50	7.8	6.2	5.4	16	12.50	8.3	6.6	5.8
16	15.00	6.0	5.0	4.4	16	15.00	7.3	5.8	5.1	16	15.00	7.8	6.2	5.4
16	20.00	5.2	4.6	4.0	16	20.00	6.7	5.3	4.6	16	20.00	7.1	5.6	4.9
24	5.00	8.0	6.3	5.5	24	5.00	9.2	7.3	6.4	24	5.00	9.8	7.8	6.8
24	6.70	7.3	5.8	5.0	24	6.70	8.4	6.7	5.8	24	6.70	8.9	7.1	6.2
24	7.50	7.0	5.5	4.8	24	7.50	8.1	6.4	5.6	24	7.50	8.6	6.8	5.0
24	10.00	6.0	5.0	4.4	24	10.00	7.3	5.8	5.1	24	10.00	7.8	6.2	5.4
24	12.50	5.4	4.7	4.1	24	12.50	6.8	5.4	4.7	24	12.50	7.2	5.8	5.0
24	15.00	4.9	4.4	3.8	24	15.00	6.4	5.1	4.4	24	15.00	6.8	5.4	4.7
24	20.00	4.3	4.0	3.3	24	20.00	5.6	4.6	4.0	24	20.00	6.2	4.9	4.3

2 1/2" x 25Ga x 33 KSI					2 1/2" x 22Ga x 33 KSI					2 1/2" x 20Ga x 33 KSI				
Spc (in.)	Wind Px psf	L120 ft.	L240 ft.	L360 ft.	Spc (in.)	Wind Px psf	L120 ft.	L240 ft.	L360 ft.	Spc (in.)	Wind Px psf	L120 ft.	L240 ft.	L360 ft.
12	5.00	13.9	11.1	9.7	12	5.00	16.1	12.8	11.2	12	5.00	17.2	13.7	11.9
12	6.70	12.7	10.1	8.8	12	6.70	14.7	11.6	10.2	12	6.70	15.6	12.4	10.8
12	7.50	12.2	9.7	8.5	12	7.50	14.1	11.2	9.8	12	7.50	15.0	11.9	10.4
12	10.00	11.1	8.8	7.7	12	10.00	12.8	10.2	8.9	12	10.00	13.7	10.8	9.5
12	12.50	10.1	8.2	7.1	12	12.50	11.9	9.4	8.3	12	12.50	12.7	10.1	8.8
12	15.00	9.2	7.7	6.7	12	15.00	11.2	8.9	7.8	12	15.00	11.9	9.5	8.3
12	20.00	8.0	7.0	6.1	12	20.00	10.2	8.1	7.1	12	20.00	10.8	8.6	7.5
16	5.00	12.7	10.1	8.8	16	5.00	14.7	11.6	10.2	16	5.00	15.6	12.4	10.8
16	6.70	11.5	9.1	8.0	16	6.70	13.3	10.6	9.2	16	6.70	14.2	11.3	9.8
16	7.50	11.1	8.8	7.7	16	7.50	12.8	10.2	8.9	16	7.50	13.7	10.8	9.5
16	10.00	9.8	8.0	7.0	16	10.00	11.6	9.2	8.1	16	10.00	12.4	9.8	8.6
16	12.50	8.8	7.4	6.5	16	12.50	10.8	8.6	7.5	16	12.50	11.5	9.1	8.0
16	15.00	8.0	7.0	6.1	16	15.00	10.2	8.1	7.1	16	15.00	10.8	8.6	7.5
16	20.00	6.9	6.3	5.5	16	20.00	9.0	7.3	6.4	16	20.00	9.8	7.8	6.8
24	5.00	11.1	8.8	7.7	24	5.00	12.8	10.2	8.9	24	5.00	13.7	10.8	9.5
24	6.70	9.8	8.0	7.0	24	6.70	11.6	9.2	8.1	24	6.70	12.4	9.8	8.6
24	7.50	9.2	7.7	6.7	24	7.50	11.2	8.9	7.8	24	7.50	11.9	9.5	8.3
24	10.00	8.0	7.0	6.1	24	10.00	10.2	8.1	7.1	24	10.00	10.8	8.6	7.5
24	12.50	7.2	6.5	5.7	24	12.50	9.3	7.5	6.6	24	12.50	10.1	8.0	7.0
24	15.00	6.5	6.1	5.3	24	15.00	8.5	7.1	6.2	24	15.00	9.5	7.5	6.6
24	20.00	5.7	5.5	4.8	24	20.00	7.4	6.4	5.6	24	20.00	8.4	6.8	6.0

This data was compiled from the 1996 edition of American Iron and Steel Institutes Cold Formed Steel Design Manual. It is FOR REFERENCE ONLY. No warranty is expressed or implied in reference to this data. If you require design data as shown above, we suggest you secure the services of an engineering firm.

Maximum Allowable Heights for Drywall Stud Sections

3 5/8" x 25Ga x 33 KSI					3 5/8" x 22Ga x 33 KSI					3 5/8" x 20Ga x 33 KSI				
Spc (in.)	Wind Px psf	L120 ft.	L240 ft.	L360 ft.	Spc (in.)	Wind Px psf	L120 ft.	L240 ft.	L360 ft.	Spc (in.)	Wind Px psf	L120 ft.	L240 ft.	L360 ft.
12	5.00	18.6	14.7	12.9	12	5.00	21.5	17.1	14.9	12	5.00	22.9	18.2	15.9
12	6.70	16.9	13.4	11.7	12	6.70	19.5	15.5	13.5	12	6.70	20.8	16.5	14.4
12	7.50	16.2	12.9	11.3	12	7.50	18.8	14.9	13.0	12	7.50	20.0	15.9	13.9
12	10.00	14.6	11.7	10.2	12	10.00	17.1	13.5	11.8	12	10.00	18.2	14.4	12.6
12	12.50	13.0	10.9	9.5	12	12.50	15.8	12.6	11.0	12	12.50	16.9	13.4	11.7
12	15.00	11.9	10.2	8.9	12	15.00	14.9	11.8	10.3	12	15.00	15.9	12.6	11.0
12	20.00	10.3	9.3	8.1	12	20.00	13.3	10.8	9.4	12	20.00	14.4	11.5	10.0
16	5.00	16.9	13.4	11.7	16	5.00	19.5	15.5	13.5	16	5.00	20.8	16.5	14.4
16	6.70	15.3	12.2	10.6	16	6.70	17.7	14.1	12.3	16	6.70	18.9	15.0	13.1
16	7.50	14.6	11.7	10.2	16	7.50	17.1	13.5	11.8	16	7.50	18.2	14.4	12.6
16	10.00	12.6	10.6	9.3	16	10.00	15.5	12.3	10.8	16	10.00	16.5	13.1	11.5
16	12.50	11.3	9.9	8.6	16	12.50	14.4	11.4	10.0	16	12.50	15.3	12.2	10.6
16	15.00	10.3	9.3	8.1	16	15.00	13.3	10.8	9.4	16	15.00	14.4	11.5	10.0
16	20.00	8.9	8.4	7.4	16	20.00	11.6	9.8	8.5	16	20.00	13.1	10.4	9.1
24	5.00	14.6	11.7	10.2	24	5.00	17.1	13.5	11.8	24	5.00	18.2	14.4	12.6
24	6.70	12.6	10.6	9.3	24	6.70	15.5	12.3	10.8	24	6.70	16.5	13.1	11.5
24	7.50	11.9	10.2	8.9	24	7.50	14.9	11.8	10.3	24	7.50	15.9	12.6	11.0
24	10.00	10.3	9.3	8.1	24	10.00	13.3	10.8	9.4	24	10.00	14.4	11.5	10.0
24	12.50	9.2	8.6	7.5	24	12.50	11.9	10.0	8.7	24	12.50	13.4	10.6	9.3
24	15.00	8.4	8.1	7.1	24	15.00	10.9	9.4	8.2	24	15.00	12.4	10.0	8.8
24	20.00	7.3	7.3	6.4	24	20.00	9.4	8.5	7.5	24	20.00	10.7	9.1	8.0

4" x 25Ga x 33 KSI					4" x 22Ga x 33 KSI					4" x 20Ga x 33 KSI				
Spc (in.)	Wind Px psf	L120 ft.	L240 ft.	L360 ft.	Spc (in.)	Wind Px psf	L120 ft.	L240 ft.	L360 ft.	Spc (in.)	Wind Px psf	L120 ft.	L240 ft.	L360 ft.
12	5.00	20.1	15.9	13.9	12	5.00	23.2	18.4	16.1	12	5.00	24.7	19.6	17.2
12	6.70	18.2	14.5	12.6	12	6.70	21.1	16.7	14.6	12	6.70	22.5	17.8	15.6
12	7.50	17.5	13.9	12.2	12	7.50	20.3	16.1	14.1	12	7.50	21.6	17.2	15.0
12	10.00	15.6	12.6	11.0	12	10.00	18.4	14.6	12.8	12	10.00	19.6	15.6	13.6
12	12.50	13.9	11.7	10.3	12	12.50	17.1	13.6	11.9	12	12.50	18.2	14.5	12.7
12	15.00	12.7	11.0	9.7	12	15.00	16.1	12.8	11.2	12	15.00	17.2	13.6	11.9
12	20.00	11.0	10.0	8.8	12	20.00	14.3	11.6	10.1	12	20.00	15.6	12.4	10.8
16	5.00	18.2	14.5	12.6	16	5.00	21.1	16.7	14.6	16	5.00	22.5	17.9	15.6
16	6.70	16.5	13.1	11.5	16	6.70	19.2	15.2	13.3	16	6.70	20.4	16.2	14.2
16	7.50	15.6	12.6	11.0	16	7.50	18.4	14.6	12.8	16	7.50	19.6	15.6	13.6
16	10.00	13.5	11.5	10.0	16	10.00	16.7	13.3	11.6	16	10.00	17.9	14.2	12.4
16	12.50	12.1	10.7	9.3	16	12.50	15.5	12.3	10.8	16	12.50	16.6	13.2	11.5
16	15.00	11.0	10.0	8.8	16	15.00	14.3	11.6	10.1	16	15.00	15.6	12.4	10.8
16	20.00	9.5	9.1	8.0	16	20.00	12.4	10.6	9.2	16	20.00	14.1	11.3	9.8
24	5.00	15.6	12.6	11.0	24	5.00	18.4	14.6	12.8	24	5.00	19.6	15.6	13.6
24	6.70	13.5	11.5	10.0	24	6.70	16.7	13.3	11.6	24	6.70	17.8	14.2	12.4
24	7.50	12.7	11.0	9.7	24	7.50	16.1	12.8	11.2	24	7.50	17.2	13.6	11.9
24	10.00	11.0	10.0	8.8	24	10.00	14.3	11.6	10.1	24	10.00	15.6	12.4	10.8
24	12.50	9.9	9.3	8.1	24	12.50	12.8	10.8	9.4	24	12.50	14.5	11.5	10.0
24	15.00	9.0	8.8	7.7	24	15.00	11.6	10.1	8.9	24	15.00	13.3	10.8	9.5
24	20.00	7.8	7.8	7.0	24	20.00	10.1	9.2	8.1	24	20.00	11.5	9.8	8.6

This data was compiled from the 1996 edition of American Iron and Steel Institutes Cold Formed Steel Design Manual. It is FOR REFERENCE ONLY. No warranty is expressed or implied in reference to this data. If you require design data as shown above, we suggest you secure the services of an engineering firm.

Maximum Allowable Heights for Drywall Stud Sections

6" x 25Ga x 33 KSI					6" x 22Ga x 33 KSI					6" x 20Ga x 33 KSI				
Spc (in.)	Wind Px psf	L120 ft.	L240 ft.	L360 ft.	Spc (in.)	Wind Px psf	L120 ft.	L240 ft.	L360 ft.	Spc (in.)	Wind Px psf	L120 ft.	L240 ft.	L360 ft.
12	5.00	27.7	22.0	19.2	12	5.00	31.7	25.2	22.0	12	5.00	33.8	26.8	23.4
12	6.70	25.1	20.0	17.4	12	6.70	28.8	22.9	20.0	12	6.70	30.7	24.4	21.3
12	7.50	23.9	19.2	16.8	12	7.50	27.7	22.0	19.2	12	7.50	29.5	23.4	20.5
12	10.00	20.7	17.4	15.2	12	10.00	25.2	20.0	17.4	12	10.00	26.8	21.3	18.6
12	12.50	18.6	16.2	14.1	12	12.50	23.4	18.5	16.2	12	12.50	24.9	19.8	17.3
12	15.00	16.9	15.2	13.3	12	15.00	21.5	17.4	15.2	12	15.00	23.4	18.6	16.3
12	20.00	14.7	13.8	12.1	12	20.00	18.6	15.9	13.9	12	20.00	20.8	16.9	14.8
16	5.00	25.1	20.0	17.4	16	5.00	28.8	22.9	20.0	16	5.00	30.7	24.4	21.3
16	6.70	22.0	18.1	15.8	16	6.70	26.2	20.8	18.1	16	6.70	27.9	22.1	19.4
16	7.50	20.7	17.4	15.2	16	7.50	25.2	20.0	17.4	16	7.50	26.8	21.3	18.6
16	10.00	18.0	15.8	13.8	16	10.00	22.8	18.1	15.9	16	10.00	24.4	19.4	16.9
16	12.50	16.1	14.7	12.9	16	12.50	20.4	16.8	14.7	16	12.50	22.6	18.0	15.7
16	15.00	14.7	13.8	12.1	16	15.00	18.6	15.9	13.9	16	15.00	20.8	16.9	14.8
16	20.00	11.4	11.4	11.0	16	20.00	16.1	14.4	12.6	16	20.00	18.0	15.4	13.4
24	5.00	20.7	17.4	15.2	24	5.00	25.2	20.0	17.4	24	5.00	26.8	21.3	18.6
24	6.70	18.0	15.8	13.8	24	6.70	22.8	18.1	15.9	24	6.70	24.4	19.4	16.9
24	7.50	16.9	15.2	13.3	24	7.50	21.5	17.4	15.2	24	7.50	23.4	18.6	16.3
24	10.00	14.7	13.8	12.1	24	10.00	18.6	15.9	13.9	24	10.00	20.8	16.9	14.8
24	12.50	12.1	12.1	11.2	24	12.50	16.6	14.7	12.9	24	12.50	18.6	15.7	13.4
24	15.00	10.1	10.1	10.1	24	15.00	15.2	13.9	12.1	24	15.00	17.0	14.8	12.9
24	20.00	7.6	7.6	7.6	24	20.00	13.1	12.6	11.0	24	20.00	14.7	13.4	11.7

This data was compiled from the 1996 edition of American Iron and Steel Institutes Cold Formed Steel Design Manual. It is FOR REFERENCE ONLY. No warranty is expressed or implied in reference to this data. If you require design data as shown above, we suggest you secure the services of an engineering firm.